

MOLYKOTE(R) DX PASTE

1. PRODUCT AND COMPANY IDENTIFICATION

Dow Corning Corporation
South Saginaw Road
Midland, Michigan 48686

24 Hour Emergency Telephone: (989) 496-5900

Customer Service: (989) 496-6000

Product Disposal Information: (989) 496-6315

CHEMTREC: (800) 424-9300

MSDS No.: 01160303

Revision Date: 2012/05/08

Generic Description: Mixture of inorganic and organic compounds

Physical Form: Paste

Color: White

Odor: Slight odor

NFPA Profile: Health 1 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

2. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS**Acute Effects**

Eye: Direct contact may cause severe irritation.

Skin: May cause moderate irritation.

Inhalation: Material is not likely to present an inhalation hazard at ambient conditions. However, if material is heated or high vapor concentration is attained, central nervous system depression may occur, which is characterized by drowsiness, dizziness, confusion or loss of coordination.

Oral: Low ingestion hazard in normal use.

Prolonged/Repeated Exposure Effects

Skin: Repeated or prolonged contact may cause defatting and drying of skin which may result in skin irritation and dermatitis.

Inhalation: No known applicable information.

Oral: Repeated ingestion or swallowing large amounts may injure internally.

Other Health Effects

This product contains a chemical(s) that has the following effect(s):
Carcinogenicity

MOLYKOTE(R) DX PASTE

See Section 11 for specific details.

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
64742-52-5	15.0 - 35.0	Hydrotreated heavy naphthenic petroleum distillate
61791-53-5	1.0 - 5.0	N-Tallow Alkyltrimethylenediamine Oleate

The above components are hazardous as defined in 29 CFR 1910.1200.

4. FIRST AID MEASURES

Eye:	Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 - 20 minutes while holding the eyelid(s) open. If contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.
Skin:	Remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Flush with lukewarm gently flowing water for 15 minutes. If irritation persists, repeat flushing. If irritation persists, obtain medical advice.
Inhalation:	If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.
Oral:	If irritation or discomfort occur, obtain medical advice.
Notes to Physician:	Treat according to person's condition and specifics of exposure.

5. FIRE FIGHTING MEASURES

Flash Point:	Not applicable.
--------------	-----------------

MOLYKOTE(R) DX PASTE

Autoignition Temperature: Not determined.

Flammability Limits in Air: Not determined.

Extinguishing Media: On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.

Fire Fighting Measures: Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire Hazards: None.

6. ACCIDENTAL RELEASE MEASURES

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See Section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

7. HANDLING AND STORAGE

Use with adequate ventilation. At temperatures above 482F/250C this material may produce highly toxic gaseous compounds such as hydrogen fluoride and perfluorohydrocarbons. Provide adequate ventilation or use the appropriate respiratory protection if the possibility of exceeding 482F/250C exists. Avoid contamination of tobacco products. Fluoropolymers on tobacco goods may cause adverse health effects by inhalation of the decomposition products. Employees should wash their hands and face before eating, drinking or using tobacco products. Avoid eye contact. Avoid skin contact. Avoid breathing vapor, mist, dust, or fumes. Keep container closed. Do not take internally.

Use reasonable care and store away from oxidizing materials. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Component Exposure Limits**

MOLYKOTE(R) DX PASTE

<u>CAS Number</u>	<u>Component Name</u>	<u>Exposure Limits</u>
64742-52-5	Hydrotreated heavy naphthenic petroleum distillate	Observe petroleum distillates limits. OSHA PEL (final rule): TWA 400 ppm.

Engineering Controls

Local Ventilation: Recommended.
General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves: Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.

Inhalation: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. IH personnel can assist in judging the adequacy of existing engineering controls.

Suitable Respirator: Respiratory protection is not needed under ambient conditions. If vapor is generated when material is heated or handled, the following is advised. General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

Personal Protective Equipment for Spills

Eyes: Use full face respirator.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

MOLYKOTE(R) DX PASTE

Inhalation/Suitable Respirator:	Respiratory protection recommended. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MHSA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
Precautionary Measures:	Avoid eye contact. Avoid skin contact. Avoid breathing vapor, mist, dust, or fumes. Keep container closed. Do not take internally. Use reasonable care.
Comments:	At temperatures above 482F/250C this material may produce highly toxic gaseous compounds such as hydrogen fluoride and perfluorohydrocarbons. Provide adequate ventilation or use the appropriate respiratory protection if the possibility of exceeding 482F/250C exists. Avoid contamination of tobacco products. Fluoropolymers on tobacco goods may cause adverse health effects by inhalation of the decomposition products. Employees should wash their hands and face before eating, drinking or using tobacco products.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form:	Paste
Color:	White
Odor:	Slight odor
Specific Gravity @ 25°C:	1.14
Viscosity:	Not determined.
Freezing/Melting Point:	Not determined.
Boiling Point:	Not determined.
Vapor Pressure @ 25°C:	Not determined.
Vapor Density:	Not determined.
Solubility in Water:	Not determined.
pH:	Not determined.
Volatile Content:	Not determined.
Flash Point:	Not applicable.
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable.
Hazardous Polymerization:	Hazardous polymerization will not occur.

MOLYKOTE(R) DX PASTE

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Phosphorous oxides. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Metal oxides. Fluorine compounds. Zinc oxide fumes. Nitrogen oxides.

11. TOXICOLOGICAL INFORMATIONComponent Toxicology Information

Inhalation of fumes from fire decomposition of polytetrafluoroethylene (Teflon) is known to cause polymer fume fever.

Special Hazard Information on Components**Carcinogens**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>	
64742-52-5	15.0 - 35.0	Hydrotreated heavy naphthenic petroleum distillate	IARC Group 1 - Carcinogenic to Humans.

12. ECOLOGICAL INFORMATIONEnvironmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

MOLYKOTE(R) DX PASTE

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

13. DISPOSAL CONSIDERATIONS**RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989) 496-6315, if additional information is required.

14. TRANSPORT INFORMATION**DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT.

Remarks: (APPLIES ONLY TO CONTAINERS LESS THAN 119 GALLONS OR 450 LITERS.)

Ocean Shipment (IMDG)

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

Hazard Technical Name: Tallowalkyltriethylene diamineoleate / Zinc Oxide

Hazard Class: 9

UN/NA Number: UN 3077

Packing Group: III

Hazard Label(s): miscellaneous

Marine Pollutant: Tallowalkyltriethylene diamineoleate
Zinc Oxide

Air Shipment (IATA)

Proper Shipping Name: Environmentally hazardous substance, solid, n.o.s.

Hazard Technical Name: Tallowalkyltriethylene diamineoleate / Zinc Oxide

Hazard Class: 9

UN/NA Number: UN 3077

MOLYKOTE(R) DX PASTE

Packing Group: III

Hazard Label(s): Miscellaneous dangerous goods

Apply Gross Wt Supplemental Label to Outer Package if shipping Limited Quantity

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical Listings**Section 302 Extremely Hazardous Substances (40 CFR 355):**

None.

Section 304 CERCLA Hazardous Substances (40 CFR 302):

None.

Section 311/312 Hazard Class (40 CFR 370):

Acute: Yes
Chronic: Yes
Fire: No
Pressure: No
Reactive: No

Section 313 Toxic Chemicals (40 CFR 372):

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
1314-13-2	1.9	Zinc oxide

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

Supplemental State Compliance Information**California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

MOLYKOTE(R) DX PASTE

Massachusetts

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
64742-55-8	5.0 - 10.0	Distillates (petroleum), hydrotreated light paraffinic ; Baseoil - unspecified
7620-77-1	3.0 - 7.0	12-Hydroxy lithium stearate
1314-13-2	1.0 - 5.0	Zinc oxide

New Jersey

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
1306-06-5	15.0 - 35.0	Tricalcium Phosphate, Hydrated
64741-96-4	15.0 - 35.0	Solvent refined heavy naphthenic distillate (petroleum)
64742-52-5	15.0 - 35.0	Hydrotreated heavy naphthenic petroleum distillate
64742-55-8	5.0 - 10.0	Distillates (petroleum), hydrotreated light paraffinic ; Baseoil - unspecified
7620-77-1	3.0 - 7.0	12-Hydroxy lithium stearate
1314-13-2	1.0 - 5.0	Zinc oxide

Pennsylvania

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
1306-06-5	15.0 - 35.0	Tricalcium Phosphate, Hydrated
64741-96-4	15.0 - 35.0	Solvent refined heavy naphthenic distillate (petroleum)
64742-52-5	15.0 - 35.0	Hydrotreated heavy naphthenic petroleum distillate
64742-55-8	5.0 - 10.0	Distillates (petroleum), hydrotreated light paraffinic ; Baseoil - unspecified
7620-77-1	3.0 - 7.0	12-Hydroxy lithium stearate
9002-84-0	1.0 - 5.0	Polytetrafluoroethylene
1314-13-2	1.0 - 5.0	Zinc oxide

MOLYKOTE(R) DX PASTE**16. OTHER INFORMATION**

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark